


COMPACT
SERIES 06E



Pipe Ports 1/4"
 Flow SCFM* 46
 4.4 Ounce Bowl
 40 Micron Element
 Relieving Type
 2-125 PSIG Range

DIMENSIONS

A	B	C	D	D†	E	E†	F
2.81	2.74	4.69	5.69	5.74	10.38	10.43	2.25

† With Auto Drain

NOTE: 2.00 Dia. hole required for panel mounting.

⚠ WARNING

Product rupture can cause serious injury.

Do not connect regulator to bottled gas.

Do not exceed maximum primary pressure rating.

TEMPERATURE & PRESSURE RATINGS:

Polycarbonate Bowl: 0 to 150 PSIG, 32°F to 125°F
Metal Bowl: 0 to 250 PSIG, 32°F to 175°F

Automatic Drain:

Optional (Interchangeable Field Conversions)
 Operating Range 10-250 PSIG

Secondary Pressure Ranges:

Standard Pressure 2 to 125 PSIG
 Low Pressure 1 to 60 PSIG
 High Pressure 2 to 250 PSIG

SPECIFICATIONS:

Filter / Regulator Body:

Bowls:
 Transparent Polycarbonate / Twist Drain PS732P
 Metal (Zinc) with Sight Gauge / Twist Drain PS735P

Filter Elements:

40 Micron Standard – Plastic PS701P
 5 Micron Optional – Plastic PS702P
 Adsorber Optional – Activated Charcoal PS731P

Mounting Bracket Kit:

(Plastic Panel Mount Nut Included) PS707P
Control Knob: Plastic P04069B


Relieving Service Kit PS710P

KIT NUMBER

Zinc

Poly Bowl / Metal Guard				Metal Bowl / Sight Gauge			
Twist Drain		Automatic Float Drain		Twist Drain		Automatic Float Drain	
1/4"	06E12A13AC	1/4"	06E16A13AC	1/4"	06E14A13AC	1/4"	06E18A13AC
3/8"	06E22A13AC	3/8"	06E26A13AC	3/8"	06E24A13AC	3/8"	06E28A13AC
1/2"	06E32A13AC	1/2"	06E36A13AC	1/2"	06E34A13AC	1/2"	06E38A13AC

STANDARD
SERIES 07E



Pipe Ports 3/8"
 Flow SCFM* 70
 7.2 Ounce Bowl
 40 Micron Element
 Relieving Type
 2-125 PSIG Range

⚠ WARNING

Product rupture can cause serious injury.

Do not connect regulator to bottled gas.

Do not exceed maximum primary pressure rating.

TEMPERATURE & PRESSURE RATINGS:

– Same as above for 06E –

SPECIFICATIONS:

Filter / Regulator Body:

Bowls:
 Transparent Polycarbonate / Twist Drain PS832P
 Metal (Zinc) with Sight Gauge / Twist Drain PS835P

Filter Elements:

40 Micron Standard – Plastic PS801P
 5 Micron Optional – Plastic PS802P
 Adsorber Optional – Activated Charcoal PS831P

Mounting Bracket Kit:

(Plastic Panel Mount Nut Included) PS807P
Control Knob: Plastic P04069B

Relieving Service Kit PS810P

KIT NUMBER

Zinc

DIMENSIONS

A	B	C	D	D†	E	E†	F
3.24	3.25	4.79	6.97	7.00	11.76	11.79	2.75

† With Auto Drain

NOTE: 2.00 Dia. hole required for panel mounting.

Poly Bowl / Metal Guard				Metal Bowl / Sight Gauge			
Twist Drain		Automatic Float Drain		Twist Drain		Automatic Float Drain	
3/8"	07E22A13AC	3/8"	07E26A13AC	3/8"	07E24A13AC	3/8"	07E28A13AC
1/2"	07E32A13AC	1/2"	07E36A13AC	1/2"	07E34A13AC	1/2"	07E38A13AC
3/4"	07E42A13AC	3/4"	07E46A13AC	3/4"	07E44A13AC	3/4"	07E48A13AC

* SCFM = Standard cubic feet per minute at 100 PSIG inlet, 90 PSIG no flow secondary setting and 10 PSIG pressure drop.