




STANDARD
SERIES 07R



Adjustment Knob
removes for
panel mounting



⚠ WARNING
Product rupture can cause serious injury.
Do not connect regulator to bottled gas.
Do not exceed maximum primary pressure rating.

TEMPERATURE & PRESSURE RATINGS:

Maximum Primary Pressure:	250 PSIG, 32°F to 175°F
Secondary Pressure Ranges:	
Standard Pressure	2 to 125 PSIG
Medium Pressure	1 to 60 PSIG
Medium Pressure	1 to 30 PSIG
Low Pressure	1 to 15 PSIG

SPECIFICATIONS:

Body:	Zinc
Bonnet:	
Plastic	PS715P
Spring – Poppet & Control:	
Steel 2-125 PSIG	P04063
Mounting Bracket Kit:	
(Plastic Panel Mount Nut Included)	PS807P
Panel Mount Nut:	
Aluminum	P04079B
Plastic	P04082
Control Knob:	
Plastic	P04069B
Relieving Service Kit	PS808P

Pipe Ports	3/8"	1/2"	3/4"
Flow SCFM §	70	90	90
Non-Rising Knob / Relieving Type			
2-125 PSIG Range			

Without Gauge		With Gauge	
3/8"	07R213AC	3/8"	07R218AC
1/2"	07R313AC	1/2"	07R318AC
3/4"	07R413AC	3/4"	07R418AC

DIMENSIONS


A	B	C	D	E
3.24	2.74	4.79	1.61	6.40

NOTE: 2.00 Dia. hole required for panel mounting. Maximum panel thickness 1/4".

HI-FLOW

SERIES P3NR

9



⚠ WARNING
Product rupture can cause serious injury.
Do not connect regulator to bottled gas.
Do not exceed maximum primary pressure rating.

TEMPERATURE & PRESSURE RATINGS:

Maximum Primary Pressure:	250 PSIG, 32°F to 175°F
Secondary Pressure Range:	2-125 PSIG

SPECIFICATIONS:

Body:	Aluminum
Bonnet:	Aluminum
Spring:	
Steel 2-125 PSIG Range	C10A1308
Mounting Bracket Kit:	P3NKA00MW
Relieving Service Kit	P3NKA00RR

Pipe Ports	3/4"	1"
Flow SCFM §	200	300
Non-Rising Knob / Relieving Type		
2-125 PSIG Range		

Without Gauge		With Gauge	
3/4"	P3NRA96BNN	3/4"	P3NRA96BNG
1"	P3NRA98BNN	1"	P3NRA98BNG

DIMENSIONS

A	A (PB)	B	C	D	E
3.62	5.91	3.62	6.38	2.08	8.46

§ SCFM = Standard cubic feet per minute at 100 PSIG inlet, 90 PSIG no flow secondary setting and 10 PSIG pressure drop.