




MINIATURE
SERIES 10F



TEMPERATURE & PRESSURE RATINGS:

Polycarbonate Bowl: 0 to 150 PSIG, 32°F to 125°F
Metal Bowl: 0 to 250 PSIG, 32°F to 175°F

SPECIFICATIONS:

Body: **KIT NUMBER**
 Zinc
Bowls: Transparent Polycarbonate / Twist Drain PS404P
 Metal (Zinc) without Sight Gauge / Twist Drain PS447BP

Filter Elements:

Borosilicate & Felt Glass Fibers
 Grade 6 Standard PS446P
 Grade 10 Optional PS456P
Mounting Bracket Kit: PS417BP

Pipe Ports 1/8" 1/4"
 Flow SCFM § 17 20
 1 Ounce Bowl
 Grade 6 Element †

DIMENSIONS


A	B	C	D	D †	E	E †	F
1.69	1.53	0.39	3.82	3.87	4.21	4.26	1.60

† With Auto Drain

Poly Bowl				Metal Bowl without Sight Gauge			
Twist Drain		Automatic Pulse Drain		Twist Drain		Automatic Pulse Drain	
1/8"	10F01ED	1/8"	10F05ED	1/8"	10F03ED	1/8"	10F07ED
1/4"	10F11ED	1/4"	10F15ED	1/4"	10F13ED	1/4"	10F17ED

ECONOMY

SERIES 15F



TEMPERATURE & PRESSURE RATINGS:

Polycarbonate Bowl: 0 to 150 PSIG, 32°F to 125°F
Metal Bowl: 0 to 250 PSIG, 32°F to 175°F
With Differential Pressure Indicator: 0 to 150 PSIG, 32°F to 125°F

SPECIFICATIONS:

Body: **KIT NUMBER**
 Zinc
Bowls: Transparent Polycarbonate / Twist Drain PS932P
 Metal (Zinc) with Sight Gauge / Twist Drain PS935P

Filter Elements:

Borosilicate & Felt Glass Fibers
 Grade 6 Standard PS924P
 Grade 10 Optional PS930P
Mounting Bracket Kit: PS943P

Pipe Ports 1/4" 3/8"
 Flow SCFM § 30 30
 2 Ounce Bowl
 Grade 6 Element †
 Differential Pressure Indicator Standard

DIMENSIONS

A	B	C	D	D †	E †	F	G
2.00	2.06	1.50	1.86	5.35	6.85	1.77	4.50

† With Twist Drain or Auto Pulse Drain

Poly Bowl / Metal Guard				Metal Bowl / Sight Gauge			
Twist Drain		Automatic Pulse Drain		Twist Drain		Automatic Pulse Drain	
1/4"	15F12EA	1/4"	15F1PEA	1/4"	15F14EA	1/4"	15F1TEA
3/8"	15F22EA	3/8"	15F2PEA	3/8"	15F24EA	3/8"	15F2TEA

† For Grade 10 Element change the 6th space from an "E" to a "H". Example: XXF01H.

§ SCFM = Standard cubic feet per minute at 90 PSIG inlet and 5 PSIG pressure drop.