




**COMPACT**  
**SERIES 11F**



**TEMPERATURE & PRESSURE RATINGS:**

- Polycarbonate Bowl:** 0 to 150 PSIG, 32°F to 125°F
- Metal Bowl:** 0 to 250 PSIG, 32°F to 175°F
- Automatic Float Drain:** 10 to 250 PSIG at 125°F or less
- With Differential Pressure Indicator:** 0 to 150 PSIG, 32°F to 125°F

**SPECIFICATIONS:**

- Body:** Zinc
- Bowls:**
  - Transparent Polycarbonate/Twist Drain PS732P
  - Metal (Zinc) with Sight Gauge/Twist Drain PS735P
- Filter Elements:**
  - Borosilicate & Felt Glass Fibers
  - Grade 6 Standard PS724P
  - Grade 10 Optional PS730P
- Mounting Bracket Kit:** PS743P

Pipe Ports	1/4"	3/8"	1/2"
Flow SCFM §	45	48	65
4.4 Ounce Bowl			
Grade 6 Element †			
Differential Pressure Indicator Standard			


**DIMENSIONS**

A	B	C	C1	D	D†	E	E†	F	G
2.81	2.74	1.46	1.81	5.69	5.74	7.15	7.20	2.25	4.50

† With Auto Drain

Poly Bowl / Metal Guard				Metal Bowl / Sight Gauge			
Twist Drain		Automatic Float Drain		Twist Drain		Automatic Float Drain	
1/4"	11F12EC	1/4"	11F16EC	1/4"	11F14EC	1/4"	11F18EC
3/8"	11F22EC	3/8"	11F26EC	3/8"	11F24EC	3/8"	11F28EC
1/2"	11F32EC	1/2"	11F36EC	1/2"	11F34EC	1/2"	11F38EC

**STANDARD**  
**SERIES 12F**



**TEMPERATURE & PRESSURE RATINGS:**

- Polycarbonate Bowl:** 0 to 150 PSIG, 32°F to 125°F
- Metal Bowl:** 0 to 250 PSIG, 32°F to 175°F
- Automatic Float Drain:** 10 to 250 PSIG at 125°F or less
- With Differential Pressure Indicator:** 0 to 150 PSIG, 32°F to 125°F

**SPECIFICATIONS:**

- Body:** Zinc
- Bowls:**
  - Transparent Polycarbonate/Twist Drain PS832P
  - Metal (Zinc) with Sight Gauge/Twist Drain PS835P
- Filter Elements:**
  - Borosilicate & Felt Glass Fibers
  - Grade 6 Standard PS824P
  - Grade 10 Optional PS830P
- Mounting Bracket Kit:** PS843P

Pipe Ports	3/8"	1/2"	3/4"
Flow SCFM §	73	75	80
7.2 Ounce Bowl			
Grade 6 Element †			
Differential Pressure Indicator Standard			

**DIMENSIONS**

A	B	C	C1	D	D†	E	E†	F	G
3.24	3.25	1.63	2.00	6.97	7.00	8.60	8.63	2.75	4.50

† With Auto Drain

Poly Bowl / Metal Guard				Metal Bowl / Sight Gauge			
Twist Drain		Automatic Float Drain		Twist Drain		Automatic Float Drain	
3/8"	12F22EC	3/8"	12F26EC	3/8"	12F24EC	3/8"	12F28EC
1/2"	12F32EC	1/2"	12F36EC	1/2"	12F34EC	1/2"	12F38EC
3/4"	12F42EC	3/4"	12F46EC	3/4"	12F44EC	3/4"	12F48EC

† For Grade 10 Element change the 6th space from an "E" to a "H". Example: XXF01H.  
 § SCFM = Standard cubic feet per minute at 90 PSIG inlet and 5 PSIG pressure drop.