


**MINIATURE**

**SERIES 14E**



**⚠ WARNING**

**Product rupture can cause serious injury.**

**Do not connect regulator to bottled gas.**

**Do not exceed maximum primary pressure rating.**

Pipe Ports	1/8"	1/4"
Flow SCFM §	16	18
1 Ounce Bowl		
5 Micron Element		
Relieving Type		
Locking Knob		
2-125 PSIG Range		

**TEMPERATURE & PRESSURE RATINGS:**

**Polycarbonate Bowl:** 0 to 150 PSIG, 32°F to 125°F  
**Metal Bowl:** 0 to 250 PSIG, 32°F to 125°F

**Secondary Pressure Ranges:**

Standard Pressure	2 to 125 PSIG
Medium Pressure	1 to 60 PSIG
Medium Pressure	1 to 30 PSIG
Low Pressure	1 to 15 PSIG

**SPECIFICATIONS:**

**Filter / Regulator Body:**

**KIT NUMBER**  
Zinc

**Bowls:**

Transparent Polycarbonate / Twist Drain	PS404P
Metal (Zinc) without Sight Gauge / Twist Drain	PS447BP

**Filter Elements:**

40 Micron Optional – Plastic	PS401P
5 Micron Standard – Plastic	PS403P
Adsorber Optional – Activated Charcoal	PS452P

**Mounting Bracket Kit:**

(Plastic Panel Mount Nut Included)	PS417BP
------------------------------------	---------

**DIMENSIONS**

A	B	C	D	D†	E	E†	F
1.62	1.58	2.42	3.79	3.84	6.21	6.06	1.60


† With Auto Drain

**NOTE:** 1.218 Dia. hole required for panel mounting.

Poly Bowl				Metal Bowl without Sight Gauge			
Twist Drain		Automatic Pulse Drain		Twist Drain		Automatic Pulse Drain	
1/8"	14E01B13FC	1/8"	14E05B13FC	1/8"	14E03B13FC	1/8"	14E07B13FC
1/4"	14E11B13FC	1/4"	14E15B13FC	1/4"	14E13B13FC	1/4"	14E17B13FC

**ECONOMY**

**SERIES 05E**



**⚠ WARNING**

**Product rupture can cause serious injury.**

**Do not connect regulator to bottled gas.**

**Do not exceed maximum primary pressure rating.**

Pipe Ports	1/4"	3/8"
Flow SCFM §	30	40
2 Ounce Bowl		
40 Micron Element		
Relieving Type		
2-125 PSIG Range		

**TEMPERATURE & PRESSURE RATINGS:**

**Polycarbonate Bowl:** 0 to 150 PSIG, 32°F to 125°F  
**Metal Bowl:** 0 to 250 PSIG, 32°F to 125°F  
**Secondary Pressure Range:** 2-125 PSIG

**SPECIFICATIONS:**

**Filter / Regulator Body:**

**KIT NUMBER**  
Zinc

**Bowls:**

Transparent Polycarbonate / Twist Drain	PS932P
Metal (Zinc) with Sight Gauge / Twist Drain	PS935P

**Filter Elements:**

40 Micron Standard – Plastic	PS901P
5 Micron Optional – Plastic	PS902P
Adsorber Optional – Activated Charcoal	PS931P

**Mounting Bracket Kit:**

(Aluminum Panel Mount Nut Included)	PS963P
Control Knob: Plastic	P04420
Relieving Service Kit	PS908P

**DIMENSIONS**

A	B	C	D†	E†	F
2.00	2.06	3.16	5.35	8.51	1.77

† With Twist or Auto Pulse Drain

**NOTE:** 1.53 Dia. hole required for panel mounting.

Poly Bowl / Metal Guard				Metal Bowl / Sight Gauge			
Twist Drain		Automatic Pulse Drain		Twist Drain		Automatic Pulse Drain	
1/4"	05E12A13AB	1/4"	05E1PA13AB	1/4"	05E14A13AB	1/4"	05E1TA13AB
3/8"	05E22A13AB	3/8"	05E2PA13AB	3/8"	05E24A13AB	3/8"	05E2TA13AB

§ SCFM = Standard cubic feet per minute at 100 PSIG inlet, 90 PSIG no flow secondary setting and 10 PSIG pressure drop.