


MINIATURE
SERIES 14F



Pipe Ports 1/8" 1/4"
 Flow SCFM § 22 24
 1 Ounce Bowl
 5 Micron Element

TEMPERATURE & PRESSURE RATINGS

Polycarbonate Bowl: 0 to 150 PSIG, 32°F to 125°F
Metal Bowl: 0 to 250 PSIG, 32°F to 175°F
Automatic Pulse Drain: 10 to 250 PSIG at 125°F or less

SPECIFICATIONS

Body: Zinc
Bowls: Transparent Polycarbonate / Twist Drain PS404P
Filter Elements: 40 Micron Optional – Plastic PS401P
 5 Micron Standard – Plastic PS403P
 Adsorber Optional – Activated Charcoal PS452P
Mounting Bracket Kit: PS417BP


DIMENSIONS

A	B	C	D	D†	E	E†	F
1.69	1.53	0.39	3.82	3.87	4.21	4.26	1.60

† With Auto Drain

Poly Bowl				Metal Bowl without Sight Gauge			
Twist Drain		Automatic Pulse Drain		Twist Drain		Automatic Pulse Drain	
1/8"	14F01BB	1/8"	14F05BB	1/8"	14F03BB	1/8"	14F07BB
1/4"	14F11BB	1/4"	14F15BB	1/4"	14F13BB	1/4"	14F17BB

ECONOMY
SERIES 05F



Pipe Ports 1/4" 3/8"
 Flow SCFM § 54 70
 2 Ounce Bowl
 40 Micron Element

TEMPERATURE & PRESSURE RATINGS

Polycarbonate Bowl: 0 to 150 PSIG, 32°F to 125°F
Metal Bowl: 0 to 250 PSIG, 32°F to 175°F
Automatic Pulse Drain: 10 to 150 PSIG at 125°F or less

SPECIFICATIONS

Automatic Pulse Drain – Plastic: PS998P
Body: Zinc
Bowls: Transparent Polycarbonate / Twist Drain PS932P
 Metal (Zinc) with Sight Gauge / Twist Drain PS935P
Filter Elements: 40 Micron Standard – Plastic PS901P
 5 Micron Optional – Plastic PS902P
 Adsorber Optional – Activated Charcoal PS931P
Mounting Bracket Kit: PS943P

DIMENSIONS

A	B	C	D†	E†	F
2.00	2.06	0.56	5.35	5.91	2.25

† With Twist Drain or Auto Pulse Drain

Poly Bowl / Metal Guard				Metal Bowl / Sight Gauge			
Twist Drain		Automatic Pulse Drain		Twist Drain		Automatic Pulse Drain	
1/4"	05F12AA	1/4"	05F1PAA	1/4"	05F14AA	1/4"	05F1TAA
3/8"	05F22AA	3/8"	05F2PAA	3/8"	05F24AA	3/8"	05F2TAA

§ SCFM = Standard cubic feet per minute at 90 PSIG inlet and 5 PSIG pressure drop.