




**ECONOMY**

**SERIES 15L**



Pipe Ports	1/4"	3/8"
Flow SCFM §	40	40
2 Ounce Bowl		

Poly Bowl / Metal Guard		Metal Bowl / Sight Gauge	
No Drain		Twist Drain	
1/4"	15L12NA	1/4"	15L14NA
3/8"	15L22NA	3/8"	15L24NA

**TEMPERATURE & PRESSURE RATINGS:**

**Polycarbonate Bowl:** 0 to 150 PSIG, 32°F to 125°F

**Metal Bowl:** 0 to 250 PSIG, 32°F to 175°F

**Suggested Lubricant:** F442 Oil

Petroleum based oil of 100 to 200 SSU viscosity at 100°F and an aniline point greater than 200°F.

(DO NOT USE OILS WITH ADDITIVES, COMPOUNDED OILS CONTAINING SOLVENTS, GRAPHITE, DETERGENTS, OR SYNTHETIC OILS.)

**Lubricator Oil**

12 Quart Case	F442003
4 Gallon Case	F442005
55 Gallon Drum	H06620

**SPECIFICATIONS:**

<b>Body:</b>		<b>KIT NUMBER</b>
<b>Bowls:</b>		Zinc
Transparent Polycarbonate without Drain	PS946P	
Metal (Zinc) with Sight Gauge / Twist Drain	PS929P	

**Sight Dome:** Polycarbonate PS740P

**Mounting Bracket Kit:** PS943P

**Pressure Fill Adapter Kit:** PS916P

**Service Kit:** PS948P


**DIMENSIONS**

A	B	C	C <sub>1</sub>	D	D <sup>†</sup>	E	E <sup>†</sup>	F	F <sub>1</sub>
2.00	2.06	2.26	3.35	5.12	5.35	7.38	7.61	1.77	0.39

† With Twist Drain

**COMPACT**

**SERIES 16L**



Pipe Ports	1/4"	3/8"	1/2"
Flow SCFM §	40	60	90
2.6 Ounce Bowl			

Poly Bowl / Metal Guard		Metal Bowl / Sight Gauge	
No Drain		Twist Drain	
1/4"	16L12BE	1/4"	16L14BE
3/8"	16L22BE	3/8"	16L24BE
1/2"	16L32BE	1/2"	16L34BE

**TEMPERATURE & PRESSURE RATINGS:**

**Polycarbonate Bowl:** 0 to 150 PSIG, 32°F to 125°F

**Metal Bowl:** 0 to 250 PSIG, 32°F to 175°F

**Suggested Lubricant:** F442 Oil

Petroleum based oil of 100 to 200 SSU viscosity at 100°F and an aniline point greater than 200°F.

(DO NOT USE OILS WITH ADDITIVES, COMPOUNDED OILS CONTAINING SOLVENTS, GRAPHITE, DETERGENTS, OR SYNTHETIC OILS.)

**Lubricator Oil**

12 Quart Case	F442003
4 Gallon Case	F442005
55 Gallon Drum	H06620

**SPECIFICATIONS:**

<b>Body:</b>		<b>KIT NUMBER</b>
<b>Bowls:</b>		Zinc
Transparent Polycarbonate without Drain	PS746P	
Metal (Zinc) w/ Sight Gauge / Twist Drain	PS729P	

**Sight Dome:** Polycarbonate PS740P

**Mounting Bracket Kit:** PS743P

**Pressure Fill Adapter Kit:** PS716P

**Service Kit:** PS748P

**DIMENSIONS**

A	B	C	D	D <sup>†</sup>	E	E <sup>†</sup>	F
2.81	2.74	2.24	5.58	5.69	7.82	7.93	2.25

† With Twist Drain

§ SCFM = Standard cubic feet per minute at 90 PSIG inlet and 5 PSIG pressure drop.