




**STANDARD  
 SERIES 17L**



Pipe Ports	3/8"	1/2"	3/4"
Flow SCFM §	60	90	90
4.9 Ounce Bowl			

Poly Bowl / Metal Guard		Metal Bowl / Sight Gauge	
No Drain		Twist Drain	
3/8"	17L22BE	3/8"	17L24BE
1/2"	17L32BE	1/2"	17L34BE
3/4"	17L42BE	3/4"	17L44BE

**TEMPERATURE & PRESSURE RATINGS:**

**Polycarbonate Bowl:** 0 to 150 PSIG, 32°F to 125°F

**Metal Bowl:** 0 to 250 PSIG, 32°F to 175°F

**Suggested Lubricant:** F442 Oil

Petroleum based oil of 100 to 200 SSU viscosity at 100°F and an aniline point greater than 200°F.

(DO NOT USE OILS WITH ADDITIVES, COMPOUNDED OILS CONTAINING SOLVENTS, GRAPHITE, DETERGENTS, OR SYNTHETIC OILS.)

**Lubricator Oil**

12 Quart Case	F442003
4 Gallon Case	F442005
55 Gallon Drum	H06620

**SPECIFICATIONS:**

**Body:**

**Bowls:**

Transparent Polycarbonate without Drain	PS846P
Metal (Zinc) with Sight Gauge / Twist Drain	PS829P

**Sight Dome:**

Polycarbonate PS740P

**Mounting Bracket Kit:**

PS843P

**Pressure Fill Adapter Kit:**

PS716P

**Service Kit:**

PS748P

**KIT NUMBER**

Zinc

**DIMENSIONS**

A	B	C	D	D †	E	E †	F
3.24	3.25	2.41	6.86	6.95	9.09	9.35	2.75

† With Twist Drain

§ SCFM = Standard cubic feet per minute at 90 PSIG inlet and 5 PSIG pressure drop.