

Application: Petroleum base hydraulic fluids and lubricating oils.
Inner Tube: Synthetic rubber.
Reinforcement: Two braids steel wire.
Cover: Synthetic rubber abrasion resistant, MSHA accepted.
Temperature Range: -40°F to +212°F
Fittings: 43 Series

BRAIDED HYDRAULIC HOSE

SERIES 351TC/ST HYDRAULIC HOSE - CONSTANT WORKING PRESSURE



| Part No. | Hose I.D. (in.) | Hose O.D. (in.) | Working Pressure (PSI) | Minimum Bend Radius (in.) | Parkrimp 43 Series | Available Reeled |
|-------------|-----------------|-----------------|------------------------|---------------------------|--------------------|------------------|
| 351TC/ST-4 | 1/4 | .51 | 4000 | 2 | + | + |
| 351TC/ST-6 | 3/8 | .67 | 4000 | 2-1/2 | + | + |
| 351TC/ST-8 | 1/2 | .80 | 4000 | 3-1/2 | + | + |
| 351TC/ST-10 | 5/8 | .93 | 4000 | 4 | + | + |
| 351TC/ST-12 | 3/4 | 1.09 | 4000 | 4-3/4 | + | + |

TC = Tough Cover
 ST = Super Tough