


**FEMALE METRIC L - SWIVEL (BALL NOSE) (ISO 8434-1)**

**SERIES 1C343**




Use with 302, 351ST, 351TC, 422, 431, 436, 451TC, 451ST, 471TC, 471ST, 482TC, 482ST and 881 hoses.

Part No.	Thread (mm)		Hose I.D. (in.)	A (in.)	C (in.)	W (mm)	B (in.)
1C343-10-6	10	M16x1,5	3/8	2.06	0.06	19	1.10
1C343-12-6	12	M18x1,5	3/8	2.23	0.10	22	1.18
1C343-15-8	15	M22x1,5	1/2	2.42	0.17	27	1.29

Note: When measuring overall length to the end of the nut, B & C dimensions must be used to calculate cut-off allowance.

**FEMALE METRIC L - SWIVEL - (24° CONE w/ O-RING) (ISO 12151-2 - SWS)**

**SERIES 1CA43**



Use with 302, 351ST, 351TC, 422, 431, 436, 451TC, 451ST, 471TC, 471ST, 482TC, 482ST and 881 hoses.

Part No.	Thread (mm)		Hose I.D. (in.)	A (in.)	C (in.)	W (mm)	B (in.)
1CA43-12-6	12	M18x1,5	3/8	2.17	0.03	22	1.02

Note: When measuring overall length to the end of the nut, B & C dimensions must be used to calculate cut-off allowance.