

<b>Application:</b>	Petroleum base hydraulic fluids and lubricating oils.
<b>Inner Tube:</b>	Nitrile.
<b>Reinforcement:</b>	One braid steel wire.
<b>Cover:</b>	Synthetic rubber abrasion resistant, MSHA accepted.
<b>Temperature Range:</b>	-40°F to +212°F (-40°C to +100°C).
<b>Fittings:</b>	43 Series

**BRAIDED HYDRAULIC HOSE**

**SERIES 482TC/ST HYDRAULIC HOSE - SAE 100R1 TYPE AT - ISO 1436-1 TYPE 1SN - EN853 TYPE 1SN**



Part No.	Hose I.D. (in.)	Hose O.D. (in.)	Working Pressure (PSI)	Minimum Bend Radius (in.)	Parkrimp 43 Series	Available Boxed* (50 ft.)	Available Reeled
482TC/ST-4	1/4	0.53	3250	2	+	+	+
482TC-5	5/16	0.59	3250	2-1/4	+	+	+
482TC/ST-6	3/8	0.69	3000	2-1/2	+	+	+
482TC/ST-8	1/2	0.82	2500	3-1/2	+	+	+
482TC/ST-10	5/8	0.94	2000	4	+	+	+
482TC/ST-12	3/4	1.09	1750	4-3/4	+	+	+
482TC/ST-16	1	1.41	1275	6	+	+	+

TC = Tough Cover  
 ST = Super Tough  
 \*482TC only.