

General Description: This hose is recommended for portable or production line welding in factories, ships, construction work, etc. Meets or exceeds RMA and CGA (Compressed Gas Association) specifications for Type VD, Grade R welding hose. The tube is non-blooming. Minimum 4:1 Design factor.

Warning! Care should be taken to avoid gouging, dragging, abrading or otherwise damaging the hose cover, which may also lead to premature hose failure. Do not attempt to repair or re-couple hose assemblies; replace all assemblies that show signs of age or abuse. Refer to RMA IP-11-5, "Welding Hose, Precautions for the Selection and Use of".

Warning! Grade R & RM for use with acetylene gas ONLY! DO NOT use with any other fuel gas. Bleed hoses when not in use for 30 minutes or longer. Couple with one inch ferrules only.

Tube and cover not oil and flame resistant.

- Features:**
- Tube: Black EPDM
 - Cover: Vulcanized twin - Green (oxygen), Red (acetylene) EPDM
 - Reinforcement: Multiple textile spirals
 - Temp. Range: -20° F to +200° F

Lengths: Exact length reels, +/- 50 ft., 90% 1 piece, 50 ft. min. length and coupled assemblies.

WELDING HOSE

SERIES 7126 SIAMEEZ® TWIN WELDING HOSE - GRADE R



Part No.	Cover Color	ID (in.)	Max WP (PSI)	Std. Pkg	Std. Pack Qty
7126-251	Red/Green	1/4	200	Reel	800 ft.
7126-381	Red/Green	3/8	200	Reel	700 ft

**7126 Assemblies
 Crimped B & B Brass fittings**

7126NLC-300	Red/Green	3/16	200	Carton	10 ea.
7126NLC-600	Red/Green	3/16	200	Carton	5 ea.
7126NLC-1200	Red/Green	3/16	200	Carton	5 ea.
7126NLF-300	Red/Green	1/4	200	Carton	10 ea.
7126NLF-600	Red/Green	1/4	200	Carton	5 ea.
7126NLF-1200	Red/Green	1/4	200	Carton	5 ea.
7126NLM-300	Red/Green	3/8	200	Carton	10 ea.
7126NLM-600	Red/Green	3/8	200	Carton	5 ea.
7126NLM-1200	Red/Green	3/8	200	Carton	5 ea.