

**General Description:** For conveyance of LP Gas products where a 3/16 in. through 1 in. ID is required. Meets or exceeds all Underwriter Laboratories (UL®) 21 requirements as well as CGA (Canadian Gas Association) Type 1, LP Gas hose requirements. 5:1 Design factor.

Can be used for natural gas with †application specific criteria. The molecules of natural gas are small, enhancing its ability to permeate through standard rubber or PVC hose constructions. The permeation process is more rapid as the working pressure increases, and natural gas accumulates with potentially dangerous consequences. Use pipe, non-permeable tubing or hose with barrier constructions to convey natural gas. Series 7132 LP Gas hose can be used for natural gas service, but **ONLY** under the following conditions:

- † **Maximum** working pressure of the application not to exceed 50 PSI.
- The application **must** be in an outside (non-enclosed) environment.
- Applications that are in an enclosed environment or greater than 50 PSI working pressure **are not recommended**.
- **Do not** use LPG hose for fuel hose in vehicles using CNG (Compressed Natural Gas).
- In Natural Gas applications, copper, brass, or other copper-containing fittings **should be** in accordance to the AGA rating of the particular apparatus.
- The hose used with Natural Gas **should be** subjected to the same rigorous tests and inspection as if it were being used with LPG.

**WARNING! For LP and †Natural Gas use only! Do not use in anhydrous ammonia or refrigeration applications! Do NOT use male swivel couplings or screw-together re-attachable fittings or any type of couplings that use O-Ring sealing surfaces!**

**Features:**

- Tube: Black Nitrile
- Cover: Perforated Black Neoprene
- Reinforcement: Multiple textile spirals
- Temp. Range: -40° F to +180° F (NOTE: The hose construction is capable of this rating, however, LP Gas should NEVER be conveyed over 140° F)

**Lengths:**

Reels, 90% 1 piece, 10% 2 piece, minimum length 50 ft. with a + 50 ft./-0 ft. reel footage tolerance.

**LP GAS HOSE**

**SERIES 7132 L.P. GAS HOSE - U.L. 21 - CGA TYPE I - SPIRAL**



Part No.	Cover Color	ID (in.)	Max WP (PSI)	Std. Pkg	Std. Pack Qty
7132-25354	Red/Green	1/4	350	Reel	700 ft.
7132-38354	Red/Green	3/8	350	Reel	550 ft.
7132-50354	Red/Green	1/2	350	Reel	450 ft.
7132-75354	Red/Green	3/4	350	Reel	300 ft.
7132-100354	Red/Green	1	350	Reel	250 ft.
<b>Series 7132 Assemblies</b>					
7132LAR16MP-1200	Red/Green	1	350	Carton	100 ft.
7132LAR16MP-1500	Red/Green	1	350	Carton	125 ft.
7132LAR16MP-1800	Red/Green	1	350	Carton	150 ft.