

**General Description:** A lightweight and flexible hose used in the transfer of gasoline, alcohol blended fuels, diesel fuels and other petroleum products. The hose is designed for full suction and discharge applications. 4:1 Design factor.

- Features:**
- Tube: Black Nitrile
  - Cover: Black Neoprene
  - Reinforcement: Multiple textile plies with helix wire
  - Temp. Range: -20° F to +180° F

**Lengths:** 100 ft.; 8 in. = 50 ft. – Lengths up to 200 ft. available on quotation.

## PETROLEUM TRANSFER HOSE

### SERIES 7216 TRANSLITE® TANK TRUCK HOSE



Part No.	ID (in.)	Reinf. Plies	OD (in.)	Min. Bend Radius	Max. Rec. WP
7216-1002	1	2	1.364	2.0	150
7216-1252	1-1/4	2	1.670	3.0	150
7216-1502	1-1/2	2	1.960	4.0	150
7216-2002	2	2	2.512	6.0	150
7216-2502	2-1/2	2	3.028	9.0	150
7216-3002	3	2	3.552	12.0	150
7216-4002	4	2	4.626	16.0	150
7216-5004	5	4	5.748	39.0	100
7216-6004	6	4	6.772	48.0	75
7216-8004	8	4	8.888	72.0	75