

General Description: This hose offers high pressure, high temperature (250° F continuous, 275° F intermittent) service in many industrial pressure washer applications. For use with Parker over-the-cover (non-skive) crimp couplings. 4:1 Design factor.

WARNING! Not for Steam Service.

- Features:**
- Tube: Black Neoprene
 - Cover: Perforated black or blue Neoprene
 - Reinforcement: One wire braid
 - Temp. Range: -40° F to +250° F/275° F

Lengths: Random lengths on nominal 500 ft. reels and 50 ft. cut lengths. Also available in gray and yellow on quotation.

PRESSURE WASHER HOSE

SERIES 7258 HURRICANE PRESSURE WASHER HOSE



Part No.	Cover Color	ID (in.)	Max WP (PSI)	Std. Pkg	Std. Pack Qty
7258-250BK	Black	1/4	3000	Reel	500 ft.
7258-250BL	Blue	1/4	3000	Reel	500 ft.
7258-380BK	Black	3/8	3000	Reel	500 ft.
7258-380BL	Blue	3/8	3000	Reel	500 ft.

Series 7258 - Assemblies

Part No.	Cover Color	Length (ft.)	ID (in.)	Max WP (PSI)	Std. Pkg	Std. Pack Qty
725825BKRS-600	Black	50	1/4	3000	Carton	5
725825BLRS-600	Blue	50	1/4	3000	Carton	5
725838BKRS-600	Black	50	3/8	3000	Carton	5
725838BLRS-600	Blue	50	3/8	3000	Carton	5