

General Description: Designed for saturated steam applications at pressures to 250 PSI and temperatures to 406° F. This hose will also handle super heated steam to 250 PSI and 450° F. The steel wire braids provide maximum strength and can be utilized as a static wire to make the hose assembly electrically conductive. **Not for use with detergents.** 10:1 Design factor (2500 PSI minimum burst) for steam applications.

WARNING! Water changes to hot water and phases of steam when subjected to heat and pressure. The greater the pressure, the higher the temperature required to achieve, maintain a steam phase. If the steam escapes, dangerous quantities of heat are released very suddenly. Hot water, low pressure steam, and high pressure steam can cause severe scalding or fatal burns.

USE ONLY STEAM HOSES DESIGNED FOR STEAM APPLICATIONS.

Warning! Failure to properly use, maintain, test and inspect steam hose assemblies can result in injury to personnel or damage to property.

- Features:**
- Tube: Black EPDM
 - Cover: Perforated Black EPDM
 - Reinforcement: Multiple wire braids
 - Temp. Range: -20° F to + 406°/450° F

Lengths: 1/2 in. through 1 in. random lengths on reels, +/- 100 ft., 5 piece max., 50 ft. min. length.
1-1/4 in. through 2 in., 50 ft. cut lengths.

STEAM HOSE

SERIES 7263 STEAM - LANCE® 250 STEAM HOSE - BLACK COVER



Part No.	Cover Color	ID (in.)	Max WP (PSI)	Std. Pkg	Std. Pack Qty
7263-502	Black	1/2	250	Carton	50 ft
7263-502A	Black	1/2	250	Reel	500 ft.
7263-752	Black	3/4	250	Carton	50 ft
7263-752A	Black	3/4	250	Reel	500 ft.
7263-1002	Black	1	250	Carton	50 ft
7263-1002A	Black	1	250	Reel	500 ft.
7263-1252	Black	1 - 1/4	250	Carton	50 ft
7263-1502	Black	1 - 1/2	250	Carton	50 ft
7263-2002	Black	2	250	Carton	50 ft