

**General Description:** Designed for saturated steam applications at pressures to 250 PSI and temperatures to 406° F. This hose will also handle super heated steam to 250 PSI and 450° F. The steel wire braids provide maximum strength and can be utilized as a static wire to make the hose assembly electrically conductive. **Not for use with detergents.** 10:1 Design factor (2500 PSI minimum burst) for steam applications.

**WARNING! Water changes to hot water and phases of steam when subjected to heat and pressure. The greater the pressure, the higher the temperature required to achieve, maintain a steam phase. If the steam escapes, dangerous quantities of heat are released very suddenly. Hot water, low pressure steam, and high pressure steam can cause severe scalding or fatal burns.**

**USE ONLY STEAM HOSES DESIGNED FOR STEAM APPLICATIONS.**

**Warning! Failure to properly use, maintain, test and inspect steam hose assemblies can result in injury to personnel or damage to property.**

- Features:**
- Tube: Black EPDM
  - Cover: Perforated Red EPDM
  - Reinforcement: Multiple wire braids
  - Temp. Range: -20° F to + 406°/450° F

**Lengths:** 1/2 in. through 1 in. random lengths on reels, +/- 100 ft., 5 piece max., 50 ft. min. length.  
 1-1/4 in. through 2 in., 50 ft. cut lengths.

**STEAM HOSE**

**SERIES 7264 STEAM - LANCE® 250 STEAM HOSE - RED COVER**



Part No.	Cover Color	ID (in.)	Max WP (PSI)	Std. Pkg	Std. Pack Qty
7264-502	Red	1/2	250	Carton	50 ft
7264-502A	Red	1/2	250	Reel	500 ft.
7264-752	Red	3/4	250	Carton	50 ft
7264-752A	Red	3/4	250	Reel	500 ft.
7264-1002	Red	1	250	Carton	50 ft