


**General Description:** This is a flexible hose that will withstand full suction and discharge pressure. It will handle a variety of liquid and solid materials such as water, slurry transfer, sewage, air, chemicals, grains and pellets. A versatile hose for agriculture, mining, construction and industry. 3:1 Design factor.

- Features:**
- Tube: Green PVC–Smooth
  - Cover: Green PVC–Smooth
  - Reinforcement: Rigid white PVC helix
  - Temp. Range: -5° F to +140° F

**Lengths:** 100 ft. coils 3/4 in. through 6 in.

**PVC HOSE**

**SERIES 7560 DYNAFLEX® PVC STANDARD DUTY SUCTION HOSE**



Part No.	Cover Color	ID (in.)	Max WP (PSI)	Std. Pkg	Std. Pack Qty
7560-750	Green	3/4	120	Coil	100 ft.
7560-1000	Green	1	120	Coil	100 ft.
7560-1250	Green	1 - 1/4	120	Coil	100 ft.
7560-1500	Green	1 - 1/2	100	Coil	100 ft.
7560-2000	Green	2	95	Coil	100 ft.
7560-2500	Green	2 - 1/2	75	Coil	100 ft.
7560-3000	Green	3	65	Coil	100 ft.
7560-4000	Green	4	55	Coil	100 ft.
7560-6000	Green	6	40	Coil	100 ft.