


General Description: Designed to handle a variety of applications where a lightweight, flexible suction/discharge hose is required. A steel helix wire combined with a thick wall construction gives the hose excellent kink, abrasion and crush resistance. The transparency allows for easy inspection of product being conveyed. Flexible to -10° F. The steel helix wire provides static conductivity. Meets CFR, Title 21 parts 170-199. 3:1 Design factor.

- Features:**
- Color: Transparent PVC
 - Construction: Multi-component PVC extrusion with helix wire
 - Temp. Range: -10° F to +120° F

Lengths: 100 ft. coils.

PVC HOSE

SERIES 7570 DYNAFLEX® PVC TRANSPARENT SUCTION/DISCHARGE HOSE - FDA



Part No.	Cover Color	ID (in.)	Max WP (PSI)	Std. Pkg	Std. Pack Qty
7570-750	Clear	3/4	100	Coil	100 ft.
7570-1000	Clear	1	85	Coil	100 ft.
7570-1250	Clear	1 - 1/4	72	Coil	100 ft.
7570-1500	Clear	1 - 1/2	72	Coil	100 ft.
7570-2000	Clear	2	72	Coil	100 ft.
7570-3000	Clear	3	57	Coil	100 ft.
7570-4000	Clear	4	36	Coil	100 ft.