

Application:	Pneumatic, petroleum base hydraulic fluid, lubricating oils and antifreeze solutions.
Inner Tube:	Synthetic rubber.
Reinforcement:	One fiber braid.
Cover:	Synthetic rubber, MSHA accepted
Hose Cover Colors:	Gray, Red, Yellow, Blue, Green, Black
Temperature Range:	Air: +158°F Water: +185°F Oil: -40°F to 212°F
Fittings:	82 Series

PNEUMATIC HOSE

SERIES 801 "PUSH-LOK®" MULTIPURPOSE HOSE



Part No.	Hose I.D. (in.)	Hose O.D. (in.)	Working Pressure (PSI)	Minimum Bend Radius (in.)	Vacuum Rating (in. of Hg)	Field Attachable 82 Series	Available Boxed (50 ft.)	Available Reeled
801-4	1/4	0.50	250	2-1/2	28	+	+	+
801-6	3/8	0.63	250	3	28	+	+	+
801-8	1/2	0.78	250	5	28	+	+	+
801-10	5/8	0.91	250	6	15	+	+	+
801-12	3/4	1.03	250	7	15	+	+	+
801-16	1	1.28	175	10	15	+	+	+

Note: Push-Lok is not recommended for any fuel, refrigerant, or for use in air conditioners and heat pump applications.
 Note: Push-Lok is not recommended for applications where extreme pulsation is encountered.