

<b>Application:</b>	Pneumatic, petroleum base hydraulic fluid, lubricating oils and antifreeze solutions.
<b>Inner Tube:</b>	PKR®
<b>Reinforcement:</b>	One fiber braid.
<b>Cover:</b>	Fire resistant fiber braid.
<b>Hose cover color:</b>	Black.
<b>Temperature Range:</b>	Air: +158°F Water: +185°F Oil: -40°F to +212°F
<b>Fittings:</b>	82 Series

**PNEUMATIC HOSE**

**SERIES 821FR “PUSH-LOK®” MULTIPURPOSE HOSE - FIRE RESISTANT COVER**



Part No.	Hose I.D. (in.)	Hose O.D. (in.)	Working Pressure (PSI)	Minimum Bend Radius (in.)	Vacuum Rating (in. of Hg)	Field Attachable 82 Series
821FR-4	1/4	0.50	350	2-1/2	28	+
821FR-6	3/8	0.63	300	3	28	+
821FR-8	1/2	0.78	300	5	28	+
821FR-12	3/4	1.03	250	7	28	+

Note: Push-Lok is not recommended for any fuel, refrigerant, or for use in air conditioners and heat pump applications.  
 Note: Push-Lok is not recommended for applications where extreme pulsation is encountered.