

Application:	Pneumatic, petroleum base hydraulic fluid, lubricating oils and antifreeze solutions.
Inner Tube:	Synthetic rubber.
Reinforcement:	One fiber braid.
Cover:	Synthetic rubber, MSHA accepted.
Hose Cover Colors include:	Red, Blue, Green, and Black.
Temperature Range:	Air: +158°F Water: +185°F Oil: -40°F to +212°F
Fittings:	82 Series

PNEUMATIC HOSE

SERIES 831 “PUSH-LOK®” MULTIPURPOSE HOSE - HEAVY DUTY



Part No.	Hose I.D. (in.)	Hose O.D. (in.)	Working Pressure (PSI)	Minimum Bend Radius (in.)	Vacuum Rating (in. of Hg)	Field Attachable 82 Series	Available Reeled
831-4	1/4	0.50	350	2-1/2	28	+	+
831-6	3/8	0.63	300	3	28	+	+
831-8	1/2	0.78	300	5	28	+	+
831-10	5/8	0.91	300	6	15	+	+
831-12	3/4	1.03	300	7	15	+	+

Note: Push-Lok is not recommended for any fuel, refrigerant, or for use in air conditioners and heat pump applications.
 Note: Push-Lok is not recommended for applications where extreme pulsation is encountered.