

4 WAY ALUMINUM

SINGLE SOLENOID PILOT-OPERATED



AC & DC Voltage

Part No.	Coil Chart	Pipe Size (NPT)	Orifice Size (In.)	CV Flow Factor	Min.	Max Pressure Differential			Fluid Temp. °F	Power Consumption (Watt)	Seal
						Air, Inert Gas (PSI)	Hot Water (PSI)	Lt. Oil 300 SSU (PSI)			
73417AKDKN00	5	NAMUR	11/64	.55	30	150	–	–	167	10	NBR
73417AKDKN7A	5	NAMUR	11/64	.55	30	150	–	–	167	10	NBR
73419AN2NNM0	5	1/4	1/4	1.0	15	150	–	–	165	10	NBR
73419AN2NN00	5	1/4	1/4	1.0	15	150	–	–	165	10	NBR

4 WAY BRASS

SINGLE SOLENOID PILOT-OPERATED



AC & DC Voltage

Part No.	Coil Chart	Pipe Size (NPT)	Orifice Size (In.)	CV Flow Factor	Min.	Max Pressure Differential			Fluid Temp. °F	Power Consumption (Watt)	Seal
						Air, Inert Gas (PSI)	Hot Water (PSI)	Lt. Oil 300 SSU (PSI)			
73417BKEPN00	5	NAMUR	1/4	1.2	30	150	–	–	167	10	NBR
73417BN2PN00	5	1/4	1/4	1.2	30	150	–	–	167	10	NBR