

**2 WAY BRASS**

**NORMALLY OPEN DIRECT ACTING**



**AC Voltage**

Part No.	Coil Chart	Pipe Size (NPT)	Orifice Size (In.)	CV Flow Factor	Min.	Max Pressure Differential			Fluid Temp. °F	Power Consumption (Watt)	Seal
						Air, Inert Gas (PSI)	Water (PSI)	Lt. Oil 300 SSU (PSI)			
04F2001106ACF	2	1/4	3/32	.17	0	300	250	230	180	11	NBR
04F2001108ACF	2	1/4	1/8	.35	0	130	110	100	180	11	NBR
04F2002118ACF	2	1/4	9/32	.96	0	30	25	20	180	11	NBR
08F2002128ADF	4	1/2	7/16	2.8	0	15	15	–	200	16	NBR

**2 WAY STAINLESS STEEL**

**NORMALLY OPEN DIRECT ACTING**



**AC Voltage**

Part No.	Coil Chart	Pipe Size (NPT)	Orifice Size (In.)	CV Flow Factor	Min.	Max Pressure Differential			Fluid Temp. °F	Power Consumption (Watt)	Seal
						Air, Inert Gas (PSI)	Water (PSI)	Lt. Oil 300 SSU (PSI)			
71295SN2KNJ1	5	1/4	3/32	.15	0	250	250	250	185	10	NBR

**DC Voltage**

Part No.	Coil Chart	Pipe Size (NPT)	Orifice Size (In.)	CV Flow Factor	Min.	Max Pressure Differential			Fluid Temp. °F	Power Consumption (Watt)	Seal
						Air, Inert Gas (PSI)	Water (PSI)	Lt. Oil 300 SSU (PSI)			
71295SN2KNJ1	5	1/4	3/32	.15	0	250	250	250	185	10	NBR