

2 WAY BRASS

NORMALLY CLOSED DIRECT ACTING



AC Voltage

Part No.	Coil Chart	Pipe Size (NPT)	Orifice Size (In.)	CV Flow Factor	Min.	Max Pressure Differential			Fluid Temp. °F	Power Consumption (Watt)	Seal
						Air, Inert Gas (PSI)	Water (PSI)	Lt. Oil 300 SSU (PSI)			
7121KBN1NF00	5	1/8	1/8	.31	0	365	365	365	165	10	PCTFE
7121KBN2NF00	5	1/4	1/8	.31	0	365	365	365	165	10	PCTFE
7121KBN2NV00	5	1/4	1/8	.31	0	145	145	145	185	10	FKM
7121KBN2QV00	5	1/4	5/32	.52	0	120	120	120	185	10	FKM
7121KBN2SV00	5	1/4	13/64	.76	0	80	80	80	185	10	FKM

DC Voltage

Part No.	Coil Chart	Pipe Size (NPT)	Orifice Size (In.)	CV Flow Factor	Min.	Max Pressure Differential			Fluid Temp. °F	Power Consumption (Watt)	Seal
						Air, Inert Gas (PSI)	Water (PSI)	Lt. Oil 300 SSU (PSI)			
7121KBN1NF00	5	1/8	1/8	.31	0	125	125	125	165	10	PCTFE
7121KBN2NF00	5	1/4	1/8	.31	0	125	125	125	165	10	PCTFE
7121KBN2NV00	5	1/4	1/8	.31	0	125	125	125	185	10	FKM
7121KBN2QV00	5	1/4	5/32	.52	0	60	60	60	185	10	FKM
7121KBN2SV00	5	1/4	13/64	.52	0	30	30	30	185	10	FKM