

2 WAY BRASS

NORMALLY CLOSED PILOT OPERATED



AC Voltage

Part No.	Coil Chart	Pipe Size (NPT)	Orifice Size (In.)	CV Flow Factor	Min.	Max Pressure Differential			Fluid Temp. °F	Power Consumption (Watt)	Seal
						Air, Inert Gas (PSI)	Water (PSI)	Lt. Oil 300 SSU (PSI)			
04F25C2122CAF	1	1/4	11/32	1.2	5	300	300	300	180	6	NBR
73216BN2MT00	5	1/4	1/4	.76	5	1500	1500	1500	210	10	PTFE
7321KBN2RN00	5	1/4	7/16	2.0	3	150	150	150	185	10	NBR
7321KBN3SN00	5	3/8	7/16	2.5	3	150	150	150	185	10	NBR
73212BN3SN00	5	3/8	1/2	2.4	5	300	300	300	185	10	NBR
06F22C2140AAF	1	3/8	5/8	3.0	5	200	135	135	180	6	NBR
06F23C2140ACF	2	3/8	5/8	4.0	0	150	150	150	180	11	NBR
73212BN4TN00	5	1/2	1/2	2.8	5	300	300	300	185	10	NBR
08F22C2140AAF	1	1/2	5/8	4.0	5	200	135	135	180	6	NBR
08F22C2140ADF	4	1/2	5/8	4.0	5	300	300	300	175	16	NBR
72218BN4UN00	5	1/2	5/8	4.0	0	100	100	100	185	10	NBR
73218BN4UN00	5	1/2	5/8	4.0	5	150	150	150	185	10	NBR
08F23C2140ACF	2	1/2	5/8	4.0	0	150	150	150	180	11	NBR
72218BN5VN00	5	3/4	3/4	5.0	0	100	100	100	185	10	NBR
12F22C2148AAF	1	3/4	3/4	5.0	5	125	125	125	180	6	NBR
73218BN5VN00	5	3/4	3/4	5.0	5	150	150	150	185	10	NBR
12F24C2148AAF	1	3/4	3/4	6.5	5	250	150	100	180	6	NBR
73212BN52N00	5	3/4	3/4	7.3	5	300	300	300	185	10	NBR
12F23C2148ACF	2	3/4	3/4	5.0	5	150	150	150	180	11	NBR
16F24C2164AAF	1	1	1	13.0	5	150	150	100	180	6	NBR
7221GBN64N00	5	1	1	11.7	0	230	230	230	185	10	NBR
73212BN63N00	5	1	1	11.0	5	300	300	300	185	10	NBR
73218BN64N00	5	1	1-1/16	13.5	5	125	125	125	185	10	NBR
20F24C2172AAF	1	1-1/4	1-1/8	15.0	5	150	125	100	180	6	NBR
24F24C2180AAF	1	1-1/2	1-1/4	22.5	5	150	125	100	180	6	NBR
7321GBN99N00	5	2	1-9/16	38.6	5	230	230	230	185	10	NBR

2 WAY BRASS

NORMALLY CLOSED PILOT OPERATED



DC Voltage

Part No.	Coil Chart	Pipe Size (NPT)	Orifice Size (In.)	CV Flow Factor	Min.	Max Pressure Differential			Fluid Temp. °F	Power Consumption (Watt)	Seal
						Air, Inert Gas (PSI)	Water (PSI)	Lt. Oil 300 SSU (PSI)			
73216BN2MT00	5	1/4	1/4	.76	5	800	800	800	210	10	PTFE
7321KBN2RN00	5	1/4	7/16	2.0	3	60	60	60	185	10	NBR
04F25C2122C3F	3	1/4	11/32	1.2	5	275	275	275	150	11.5	NBR
7321KBN3SN00	5	3/8	7/16	2.5	3	60	60	60	185	10	NBR
73212BN3SN00	5	3/8	1/2	2.4	5	300	300	300	185	10	NBR
06F22C2140A3F	3	3/8	5/8	3.0	5	100	100	100	150	11.5	NBR
72218BN4UN00	7	1/2	5/8	4.0	0	40	40	40	185	22	NBR
73218BN4UN00	5	1/2	5/8	4.0	5	150	150	150	185	10	NBR
73212BN4TN00	5	1/2	1/2	2.8	5	300	300	300	185	10	NBR
12F22C2148A3F	3	3/4	3/4	5.0	5	90	90	75	150	11.5	NBR
72218BN5VN00	7	3/4	3/4	5.0	0	40	40	40	185	22	NBR
73218BN5VN00	5	3/4	3/4	5.0	5	150	150	150	185	10	NBR
73212BN52N00	5	3/4	3/4	7.3	5	300	300	300	185	10	NBR
16F24C2164A3F	3	1	1	13.0	5	125	125	125	150	11.5	NBR
7221GBN64N00	7	1	1	11.7	0	85	85	85	185	22	NBR
73212BN63N00	5	1	1	11.0	5	300	300	300	185	10	NBR
73218BN64N00	5	1	1-1/16	13.5	5	125	125	125	185	10	NBR
20F24C2172A3F	3	1-1/4	1-1/8	15.0	5	125	125	125	150	11.5	NBR