

**3 WAY BRASS**

**NORMALLY CLOSED DIRECT ACTING**



**AC Voltage**

Part No.	Coil Chart	Pipe Size (NPT)	Orifice Size (In.)	CV Flow Factor	Min.	Max Pressure Differential			Fluid Temp. °F	Power Consumption (Watt)	Seal
						Air, Inert Gas (PSI)	Water (PSI)	Lt. Oil 300 SSU (PSI)			
7131KBN2JV00	5	1/4	5/64 3/32	.17 .24	0	1150	1150	150	185	10	FKM
7131TBN2JV00	5	1/4	5/64 1/8	.17 .31	0	150	150	150	185	10	FKM
7131TBN2LV00	5	1/4	3/32 9/64	.24 .38	0	110	110	110	185	10	FKM

**DC Voltage**

Part No.	Coil Chart	Pipe Size (NPT)	Orifice Size (In.)	CV Flow Factor	Min.	Max Pressure Differential			Fluid Temp. °F	Power Consumption (Watt)	Seal
						Air, Inert Gas (PSI)	Water (PSI)	Lt. Oil 300 SSU (PSI)			
7131KBN2JV00	5	1/4	5/64 3/32	.17 .24	0	150	150	150	185	10	FKM
7131TBN2JV00	5	1/4	5/64 1/8	.17 .31	0	150	150	150	185	10	FKM
7131TBN2LV00	5	1/4	3/32 9/64	.24 .38	0	110	110	110	185	10	FKM