

3 WAY BRASS

NORMALLY CLOSED PILOT OPERATED



AC Voltage

Part No.	Coil Chart	Pipe Size (NPT)	Orifice Size (in.)	CV Flow Factor	Min.	Max Pressure Differential			Fluid Temp. °F	Power Consumption (Watt)	Seal
						Air, Inert Gas (PSI)	Water (PSI)	Lt. Oil 300 SSU (PSI)			
73317BN2PN00	5	1/4	1/4	1.20	30	150	–	–	167	10	NBR
73312BN3RNJO	5	3/8	3/8	2.1	10	180	180	180	185	10	NBR
73312BN4UNJO	5	1/2	1/2	3.60	10	180	180	180	185	10	NBR
73312BN52NJO	5	3/4	3/4	7.3	10	180	180	180	185	10	NBR

DC Voltage

Part No.	Coil Chart	Pipe Size (NPT)	Orifice Size (in.)	CV Flow Factor	Min.	Max Pressure Differential			Fluid Temp. °F	Power Consumption (Watt)	Seal
						Air, Inert Gas (PSI)	Water (PSI)	Lt. Oil 300 SSU (PSI)			
73317BN2PN00	5	1/4	1/4	1.20	30	150	–	–	167	10	NBR
73312BN3RNJO	5	3/8	3/8	2.1	10	180	180	180	185	10	NBR
73312BN4UNJO	5	1/2	1/2	3.60	10	180	180	180	185	10	NBR
73312BN52NJO	5	3/4	3/4	7.3	10	180	180	180	185	10	NBR