

3 WAY BRASS

MULTIPURPOSE DIRECT ACTING



AC Voltage

Part No.	Coil Chart	Pipe Size (NPT)	Orifice Size (In.)	CV Flow Factor		Max Pressure Differential			Fluid Temp. °F	Power Consumption (Watt)	Seal
					Min.	Air, Inert Gas (PSI)	Hot Water (PSI)	Lt. Oil 300 SSU (PSI)			
7133TBN2JV00	5	1/4	5/64	.17	0	100	100	100	185	10	FKM

DC Voltage

Part No.	Coil Chart	Pipe Size (NPT)	Orifice Size (In.)	CV Flow Factor		Max Pressure Differential			Fluid Temp. °F	Power Consumption (Watt)	Seal
					Min.	Air, Inert Gas (PSI)	Hot Water (PSI)	Lt. Oil 300 SSU (PSI)			
7133TBN2JV00	5	1/4	5/64	.17	0	100	100	100	185	10	FKM

3 WAY STAINLESS STEEL

MULTIPURPOSE DIRECT ACTING



AC Voltage

Part No.	Coil Chart	Pipe Size (NPT)	Orifice Size (In.)	CV Flow Factor		Max Pressure Differential			Fluid Temp. °F	Power Consumption (Watt)	Seal	
					Min.	Air, Inert Gas (PSI)	Hot Water (PSI)	Lt. Oil 300 SSU (PSI)				
71335SN2ANJ1	5	1/4	1/32 1/32	.024	.024	0	400	400	400	185	10	NBR
71335SN2ENJ1	5	1/4	3/64 3/64	.052	.052	0	180	180	180	185	10	NBR
71335SN2GNJ1	5	1/4	1/16 1/16	.095	.095	0	115	115	115	185	10	NBR
71335SN2KNJ1	5	1/4	3/32 3/32	.17	.17	0	80	80	80	185	10	NBR

DC Voltage

Part No.	Coil Chart	Pipe Size (NPT)	Orifice Size (In.)	CV Flow Factor		Max Pressure Differential			Fluid Temp. °F	Power Consumption (Watt)	Seal	
					Min.	Air, Inert Gas (PSI)	Hot Water (PSI)	Lt. Oil 300 SSU (PSI)				
71335SN2ANJ1	5	1/4	1/32 1/32	.024	.024	0	400	400	400	185	10	NBR
71335SN2ENJ1	5	1/4	3/64 3/64	.052	.052	0	180	180	180	185	10	NBR
71335SN2GNJ1	5	1/4	1/16 1/16	.095	.095	0	115	115	115	185	10	NBR
71335SN2KNJ1	5	1/4	3/32 3/32	.17	.17	0	80	80	80	185	10	NBR