

3 WAY STAINLESS STEEL

NORMALLY OPEN DIRECT ACTING



AC Voltage

Part No.	Coil Chart	Pipe Size (NPT)	Orifice Size (In.)	CV Flow Factor	Min.	Max Pressure Differential			Fluid Temp.°F	Power Consumption (Watt)	Seal
						Air, Inert Gas (PSI)	Hot Water (PSI)	Lt. Oil 300 SSU (PSI)			
71395SN2ENJ1	5	1/4	1/16 3/64	.10 .05	0	250	250	250	185	10	NBR
71395SN2GNJ1	5	1/4	1/8 1/16	.28 .10	0	150	150	150	185	10	NBR

DC Voltage

Part No.	Coil Chart	Pipe Size (NPT)	Orifice Size (In.)	CV Flow Factor	Min.	Max Pressure Differential			Fluid Temp.°F	Power Consumption (Watt)	Seal
						Air, Inert Gas (PSI)	Hot Water (PSI)	Lt. Oil 300 SSU (PSI)			
71395SN2ENJ1	5	1/4	1/16 3/64	.10 .05	0	250	250	250	185	10	NBR
71395SN2GNJ1	5	1/4	1/8 1/16	.28 .10	0	150	150	150	185	10	NBR