

4 WAY BRASS

SINGLE SOLENOID DIRECT ACTING



AC Voltage

Part No.	Coil Chart	Pipe Size (NPT)	Orifice Size (In.)	CV Flow Factor	Min.	Max Pressure Differential			Fluid Temp.°F	Power Consumption (Watt)	Seal
						Air, Inert Gas (PSI)	Water (PSI)	Lt. Oil 300 SSU (PSI)			
71417BN2SN00	below	1/4	3/16	.75	0	125	125	125	160	24	NBR
04F48S2106ACF	2	1/4	1/16 3/32	.09 .09	10	150	150	150	180	11	NBR

DC Voltage

Part No.	Coil Chart	Pipe Size (NPT)	Orifice Size (In.)	CV Flow Factor	Min.	Max Pressure Differential			Fluid Temp.°F	Power Consumption (Watt)	Seal
						Air, Inert Gas (PSI)	Water (PSI)	Lt. Oil 300 SSU (PSI)			
04F48S2106A3F	3	1/4	1/16 3/32	.09 .09	10	100	100	100	104	11.5	NBR



Skinner Valve™	Voltage	1/2" NPT Conduit*
71417BN2SN00 24 Watts, Class H	110/50, 120/60	C8GLP3
	220/50, 240/60	C8GLQ3

*18" Lead Wires, Nema 1, 2, 3, 4, 4X