

**2 WAY BRASS**

**NORMALLY OPEN PILOT OPERATED**



**AC Voltage**

Part No.	Coil Chart	Pipe Size (NPT)	Orifice Size (In.)	CV Flow Factor	Min.	Max Pressure Differential			Fluid Temp. °F	Power Consumption (Watt)	Seal
						Air, Inert Gas (PSI)	Water (PSI)	Lt. Oil 300 SSU (PSI)			
06F2302140ACF	2	3/8	5/8	3.0	0	150	150	150	180	11	NBR
08F2302140ACF	2	1/2	5/8	4.0	0	150	150	150	180	11	NBR
16F2402164ACF	2	1	1	13.0	5	125	125	125	180	11	NBR
24F2402180ACF	2	1-1/2	1-1/4	22.5	5	125	125	125	180	11	NBR

**DC Voltage**

Part No.	Coil Chart	Pipe Size (NPT)	Orifice Size (In.)	CV Flow Factor	Min.	Max Pressure Differential			Fluid Temp. °F	Power Consumption (Watt)	Seal
						Air, Inert Gas (PSI)	Water (PSI)	Lt. Oil 300 SSU (PSI)			
08F2302140A3F	3	1/2	5/8	4.0	0	125	125	80	150	11.5	NBR
12F23021480A3F	3	3/4	3/4	5.5	0	125	125	80	150	11.5	NBR

**2 WAY STAINLESS STEEL**

**NORMALLY OPEN PILOT OPERATED**



**AC Voltage**

Part No.	Coil Chart	Pipe Size (NPT)	Orifice Size (In.)	CV Flow Factor	Min.	Max Pressure Differential			Fluid Temp. °F	Power Consumption (Watt)	Seal
						Air, Inert Gas (PSI)	Water (PSI)	Lt. Oil 300 SSU (PSI)			
12F2306148ACF	2	3/4	3/4	5.5	0	150	150	150	180	11	NBR