

**Triple-Lok Convertible  
Sleeve Connections**


Fitting Dash Size	Tube O.D. (mm)	Metric Tube Sleeve Part No.	Nut Part No.
-4	6	TXS6	4 BTX-S
-5	8	5 TX-S	5 BTX-S
-6	10	TXS10	6 BTX-S
-8	12	TXS12	8 BTX-S
-10	14	TXS14	10 BTX-S
-10	15	TXS15	10 BTX-S
-10	16	10 TX-S	10 BTX-S
-12	18	TXS18	12 BTX-S
-12	20	20-12 TX-S	20-12 BTX-S
-14	22	TXS22	14 BTX-S
-16	25	TXS25	16 BTX-S
-20	28	TXS28	20 BTX-S
-20	30	TXS30	20 BTX-S
-20	32	TXS32	20 BTX-S
-24	35	TXS35	24 BTX-S
-24	38	24 TX-S	24 BTX-S

**Wall Thickness Chart  
for Inch Tubing**

Fitting Dash Size	O.D. (in.)	Wall Thickness – Inch Tube		
		Min. (in.)	(in.)	Max.
-2	1/8	0.010	–	0.035
-3	3/16	0.010	–	0.035
-4	1/4	0.020	–	0.065
-5	5/16	0.020	–	0.065
-6	3/8	0.020	–	0.065
-8	1/2	0.028	–	0.083
-10	5/8	0.035	–	0.095
-10	5/8	0.035	–	0.095
-10	5/8	0.035	–	0.095
-12	3/4	0.035	–	0.109
-12	3/4	0.035	–	0.109
-14	7/8	0.035	–	0.109
-16	1	0.035	–	0.120
-20	1 1/4	0.049	–	0.120
-20	1 1/4	0.049	–	0.120
-24	1 1/2	0.049	–	0.120
-32	2	0.058	–	0.134

**NUT 37° FLARE**

**SERIES BTX**



Part No.	End Size (in.)	T6 UN/UNF-2B	C Hex (in.)	D (in.)	L (in.)	Standard From Stock		
						-S	-SS	-B
4 BTX	1/4	7/16-20	9/16	0.31	0.62	+	+	+
5 BTX	5/16	1/2-20	5/8	0.38	0.68	+		
6 BTX	3/8	9/16-18	11/16	0.44	0.73	+	+	+
8 BTX	1/2	3/4-16	7/8	0.57	0.85	+	+	+
10 BTX	5/8	7/8-14	1	0.70	0.98	+		
12 BTX	3/4	1 1/16-12	1 1/4	0.84	1.03	+	+	
14 BTX	7/8	1 3/16-12	1 3/8	0.96	1.09	+		
16 BTX	1	1 5/16-12	1 1/2	1.09	1.13	+		
20 BTX	1 1/4	1 5/8-12	2	1.35	1.23	+		