


MALE CONNECTOR 37° FLARE - NPTF

SERIES FTX



Part No.	End Size		C Hex (in.)	L (in.)	Standard Dynamic Pressure (x 1,000 PSI)		
	1 (in.)	2 NPTF			-S	-SS	-B
4 FTX	1/4	1/8-27	1/2	1.22	6.0	6.0	3.3
4-4 FTX	1/4	1/4-18	9/16	1.42	6.0	6.0	3.3
4-6 FTX	1/4	3/8-18	3/4	1.44	6.0		
5-4 FTX	5/16	1/4-18	9/16	1.42	6.0		
6 FTX	3/8	1/4-18	5/8	1.43	6.0	6.0	3.3
6-2 FTX	3/8	1/8-27	5/8	1.24	6.0		
6-6 FTX	3/8	3/8-18	3/4	1.44	6.0	6.0	3.3
6-8 FTX	3/8	1/2-14	7/8	1.69	6.0		
8 FTX	1/2	3/8-18	13/16	1.53	6.0		3.3
8-4 FTX	1/2	1/4-18	13/16	1.53	6.0		
8-8 FTX	1/2	1/2-14	7/8	1.78	6.0	6.0	3.3
8-12 FTX	1/2	3/4-14	1 1/8	1.85	5.5		
10 FTX	5/8	1/2-14	15/16	1.89	5.0		
12 FTX	3/4	3/4-14	1 1/8	2.06	5.0	5.0	2.6
12-8 FTX	3/4	1/2-14	1 1/8	2.06	5.0		
12-16 FTX	3/4	1-11 1/2	1 3/8	2.25	5.0		
16 FTX	1	1-11 1/2	1 3/8	2.30	4.5		2.0
16-12 FTX	1	3/4-14	1 3/8	2.11	4.5		
20 FTX	1 1/4	1 1/4-11 1/2	1 11/16	2.45	3.0		