


MALE CONNECTOR 24° FLARELESS - BSPP

SERIES GE-R-ED



| Part No. | End Size | | I 1 (mm) | S1 (mm) | Standard Pressure Rating (bar) | |
|-------------|-----------|-----------|-------------|------------|--------------------------------|------------|
| | 1 (mm) | 2 BSPP | | | EO CF | EO-2 CF |
| GE04LLRED | 4 | G 1/8 A | 9.5 | 14 | | 100 |
| GE06LRED | 6 | G 1/8 A | 8.5 | 14 | 315 | |
| GE06LR1/4ED | 6 | G 1/4A | 10.0 | 19 | 315 | |
| GE08LR1/8ED | 8 | G 1/8 A | 9.5 | 14 | | 315 |
| GE08LRED | 8 | G 1/4A | 10.0 | 19 | 315 | |
| GE08LR3/8ED | 8 | G 3/8 A | 11.5 | 22 | | 315 |
| GE10LRED | 10 | G 1/4A | 11.0 | 19 | 315 | |
| GE10LR3/8ED | 10 | G 3/8 A | 12.5 | 22 | 315 | |
| GE10LR1/2ED | 10 | G 1/2 A | 13.0 | 27 | | 315 |
| GE12LRED | 12 | G 3/8 A | 12.0 | 22 | 315 | |
| GE12LR1/2ED | 12 | G 1/2 A | 14.0 | 27 | 315 | |
| GE15LR3/8ED | 15 | G 3/8 A | 12.0 | 24 | | 315 |
| GE15LRED | 15 | G 1/2 A | 14.0 | 27 | 315 | 315 |
| GE18LRED | 18 | G 1/2 A | 14.0 | 27 | | 315 |
| GE18LR3/4ED | 18 | G 3/4 A | 16.0 | 32 | 315 | 315 |
| GE28LRED | 28 | G1 A | 18.0 | 41 | | 160 |
| GE35LRED | 35 | G1 1/4A | 20.0 | 50 | | 160 |
| GE42LRED | 42 | G1 1/2 A | 22.0 | 55 | | 160 |
| GE08SRED | 8 | G 1/4A | 15.0 | 19 | 630 | |
| GE16SRED | 16 | G 1/2 A | 18.5 | 27 | 400 | |
| GE20SRED | 20 | G 3/4 A | 20.5 | 32 | 400 | |

For EO-2 part number, insert "Z" between size and pressure series. Example: GE06ZLREDA3C