




HI-FLOW

SERIES L606



| | | | |
|---------------|-----|--------|--------|
| Pipe Ports | 1" | 1-1/4" | 1-1/2" |
| Flow SCFM § | 350 | 475 | 525 |
| 64 Ounce Bowl | | | |

| Metal Bowl | |
|------------|----------|
| No Drain | |
| 1 | L606-08G |
| 1-1/4" | L606-10G |
| 1-1/2" | L606-12G |

TEMPERATURE & PRESSURE RATINGS:

64 Oz. Bowl: 0 to 150 PSIG, 32°F to 120°F
Suggested Lubricant: F442 Oil

Petroleum based oil of 100 to 200 SSU viscosity at 100°F and an aniline point greater than 200°F.
 (DO NOT USE OILS WITH ADDITIVES, COMPOUNDED OILS CONTAINING SOLVENTS, GRAPHITE, DETERGENTS, OR SYNTHETIC OILS.)

| | |
|-----------------------|---------|
| Lubricator Oil | |
| 12 Quart Case | F442003 |
| 4 Gallon Case | F442005 |
| 55 Gallon Drum | H06620 |

SPECIFICATIONS:
Body: Zinc

| | |
|--|------------|
| Bowl: Aluminum – 64 Ounce | PBK606X30B |
| Mounting Bracket Kit: 1" Ported Body Only | SA200CW57 |

DIMENSIONS


| Port Size | A | B | C | D | E | F |
|----------------|------|------|------|------|-------|------|
| 1" | 4.06 | 4.97 | 2.63 | 9.40 | 12.02 | 2.50 |
| 1-1/4", 1-1/2" | 4.81 | 5.00 | 2.84 | 9.78 | 12.80 | 2.50 |

DIMENSIONS

| A | A ₁ | B | C | D | E | F |
|------|----------------|------|------|-------|-------|------|
| 4.81 | 6.25 | 5.28 | 2.84 | 10.44 | 13.28 | 6.50 |

HI-FLOW

SERIES 09L



| | |
|-------------|------|
| Pipe Ports | 2" |
| Flow SCFM § | 1000 |

| Metal Bowl / Sight Gauge | | |
|--------------------------|---------|------------|
| Manual Drain | | |
| 2" | 09L84BA | 1 Qt. Bowl |
| 2" | 09L8PBA | 3 Qt. Bowl |

TEMPERATURE & PRESSURE RATINGS:

Metal Bowl: 0 to 150 PSIG, 32°F to 150°F
Suggested Lubricant: F442 Oil

Petroleum based oil of 100 to 200 SSU viscosity at 100°F and an aniline point greater than 200°F.
 (DO NOT USE OILS WITH ADDITIVES, COMPOUNDED OILS CONTAINING SOLVENTS, GRAPHITE, DETERGENTS, OR SYNTHETIC OILS.)

| | |
|-----------------------|---------|
| Lubricator Oil | |
| 12 Quart Case | F442003 |
| 4 Gallon Case | F442005 |
| 55 Gallon Drum | H06620 |

SPECIFICATIONS:
Body: Zinc Alloy, Die Cast

| | |
|---|---------|
| Bowls: Metal (Aluminum) with Sight Gauge / Twist Drain | PS612P* |
| Sight Dome: Polycarbonate | PS613P |
| * 1 Quart Bowl | |

DIMENSIONS

| 1 Quart Size | | | 3 Quart Size | | | | |
|--------------|-------|------|--------------|------|------|------|------|
| A | B | C | A | B | C | D | E |
| 5.50 | 10.40 | 2.64 | 5.50 | 9.44 | 2.64 | 6.00 | 7.12 |

§ SCFM = Standard cubic feet per minute at 90 PSIG inlet and 5 PSIG pressure drop.