

NYLON TUBING

SERIES N: FLEXIBLE

General Description: Parflex flexible nylon tubing is carefully made from high-grade, abrasion resistant, heat and light stabilized nylon. Resistance to stress cracking greatly exceeds that of ordinary nylon tubing. Parflex nylon also exhibits extremely low level water absorption.

Chemical resistant Parflex nylon tubing has the additional benefits of better flexibility, lighter weight and resistance to flexural fatigue. Operating temperatures, depending upon conditions, are -65° F to +200° F continuous.

Available in natural (NN) and black (NB). Black tubing is recommended for use outdoors and in sunlit areas.

Fitting


Recommendation: Parker True Seal™ fittings and Parker Fast & Tite® fittings.

Part No.	Color	Nom. Tube O.D.	Nom. Tube I.D.	Avg. Wall Thickness	*Working Pressure at 73°F psi	Min. Burst Pressure at 73°F psi	Min. Bend Radius (in.)	Std. Reel Length (ft.)
NN-2-016	Natural	1/8	.093	.016	250	1000	1/4	250
NB-2-016	Black	1/8	.093	.016	250	1000	1/4	250
NN-2-031	Natural	1/8	.064	.031	500	2000	1/4	250
NB-2-031	Black	1/8	.064	.031	500	2000	1/4	250
NN-2.5-025	Natural	5/32	.106	.025	250	1000	1/2	250
NB-2.5-025	Black	5/32	.106	.025	250	1000	1/2	250
NN-3-025	Natural	3/16	.138	.025	250	1000	5/8	250
NB-3-025	Black	3/16	.138	.025	250	1000	5/8	250
NN-3-046	Natural	3/16	.096	.046	500	2000	7/16	250
NB-3-046	Black	3/16	.096	.046	500	2000	7/16	250
NN-4-035	Natural	1/4	.180	.035	250	1000	7/8	250
NB-4-035	Black	1/4	.180	.035	250	1000	7/8	250
NN-4-040	Natural	1/4	.170	.040	310	1250	7/8	250
NB-4-040	Black	1/4	.170	.040	310	1250	7/8	250
NN-4-062	Natural	1/4	.127	.062	500	2000	1/2	250
NB-4-062	Black	1/4	.127	.062	500	2000	1/2	250
NN-5-040	Natural	5/16	.233	.040	250	1000	1-1/8	250
NB-5-040	Black	5/16	.233	.040	250	1000	1-1/8	250
NN-6-050	Natural	3/8	.275	.050	250	1000	1-1/8	250
NB-6-050	Black	3/8	.275	.050	250	1000	1-1/8	250
NN-6-093	Natural	3/8	.190	.093	500	2000	3/4	250
NN-8-062	Natural	1/2	.375	.062	250	1000	1-1/4	250
NB-8-062	Black	1/2	.375	.062	250	1000	1-1/4	250
NN-8-124	Natural	1/2	.253	.124	500	2000	1	250
NN-8-124-000	Natural	1/2	.253	.124	500	2000	1	250

*Suggested working pressure is 1/4 of burst pressure.

HOW TO ORDER

Example: Order by tubing part number and name



- 100 Ft. bunch coils**
- Colors (except natural and black)
- Wall thickness in thousandths of an inch
- Tube O.D. in sixteenths of an inch
- Color: Natural or Black Nylon

**NEW – Series N nylon tubing is now available in 100 ft. bunch coil package lengths. To order, add suffix 0100 to part number. Example: NN-4-035-0100

