

**FAST-STOR® HOSE AND FITTINGS**

**FAST-STOR® AIR HOSE**

**General Description:** Fast-Stor® Self Retracting Air Hose, from Parflex, is manufactured from an extremely tough, abrasion resistant nylon. FAST-STOR hose has excellent memory characteristics over a wide temperature range for long service life in the most rugged applications. The SAFETY YELLOW color of FAST-STOR is highly desirable due to U.S. Government OSHA directives.

Service temperature range from -40°F to +200°F.

**FAST-STOR ASSEMBLIES**



Part No.	Fast-Stor Hose I.D.	Total Length of Hose	Usable Length	Fitting End #1	Fitting End #2 Live Swivel	Max. Working Pressure psi*	Min. Burst at 73°F
A0312-MC4-ML4	3/16	12'	9'	1/4" MPT	1/4" MPT	170	680
A0325-MC4-ML4	3/16	25'	18'	1/4" MPT	1/4" MPT	170	680
A0350-MC4-ML4	3/16	50'	38'	1/4" MPT	1/4" MPT	170	680
A0412-MC4-ML4	1/4	12'	9'	1/4" MPT	1/4" MPT	170	680
A0425-MC4-ML4	1/4	25'	18'	1/4" MPT	1/4" MPT	170	680
A0450-MC4-ML4	1/4	50'	38'	1/4" MPT	1/4" MPT	170	680
A0612-MC6-ML6	3/8	12'	9'	3/8" MPT	3/8" MPT	170	680
A0625-MC6-ML6	3/8	25'	18'	3/8" MPT	3/8" MPT	170	680
A0650-MC6-ML6	3/8	50'	38'	3/8" MPT	3/8" MPT	170	680
A0812-MC8-ML8	1/2	12'	9'	1/2" MPT	1/2" MPT	170	680
A0825-MC8-ML8	1/2	25'	18'	1/2" MPT	1/2" MPT	170	680
A0850-MC8-ML8	1/2	50'	38'	1/2" MPT	1/2" MPT	170	680

\*Maximum working pressure listed at 75°F or lower and based on safety factor of 4:1 over burst.