

**General Description:** Microglass filter has a higher dirt-holding capacity for longer usable filter life. Elements are interchangeable with major brands of the same size: 1-12" thread for 20 GPM and 1 1/2-16" thread for 50 GPM models. Dual Buna N seals resist leaks up to 150 psi, while keeping filtered and incoming fluid from mixing. Head has 1/8" NPTF port for use with optional gauge. Use in hydraulic systems with petroleum-based fluids.

- Features:**
- Max. pressure 150 psi
  - Max. temperature 225°F
  - Cast aluminum head mounts securely to in-line piping
  - 15 psi bypass spring

**HYDRAULIC FILTERS**

**HYDRAULIC RETURN LINE SPIN-ON FILTERS**



Complete Filters Part No.	Ports NPT (in.)	Max. GPM	Filter Media	Microns	Replacement Elements Part No.
12AT03CN15BBH	3/4	20	Cellulose	3	926543
12AT10CN15BBH	3/4	20	Cellulose	10	921999
12AT10BN15BBH	3/4	20	Microglass	10	928763
12AT20BN15BBH	3/4	20	Microglass	20	928764
12AT25CN15BBH	3/4	20	Cellulose	25	925023
50AT03CN15BBH	1/4	50	Cellulose	3	926541
50AT10CN15BBH	1 1/4	50	Cellulose	10	926169
50AT10BN15BBH	1 1/4	50	Microglass	10	928766
50AT20BN15BBH	1 1/4	50	Microglass	20	928767
50AT25CN15BBH	1 1/4	50	Cellulose	25	926170